

## **JAYPRO SPORTS**

## CLUB SOCCER GOAL, CSG-618 LIST OF MATERIALS

PIECE NO.	PART NO.	DESCRIPTION	QTY
1	CSG6181	CROSSBAR	2
2	CSG6182	UPRIGHT/SIDE FRAME	4
3	HS294	HEX HEAD BOLT 3/8"-16 x 4 ½"	4
4	HW5022	FENDER WASHER 13/32" x 1 <sup>1</sup> / <sub>2</sub> "	8
5	HN1230	NYLON LOCK NUT 3/8"-16	4

## ASSEMBLY INSTRUCTIONS

- 1) FIRST, POSITION UPRIGHTS FAR ENOUGH APART FROM EACH OTHER TO ALLOW FOR CROSSBAR TO BE ASSEMBLED.
- 2) NEXT, (TO BE ASSEMBLED BY TWO ADULTS) STAND UPRIGHTS IN VERTICAL POSITION AND ASSEMBLE CROSSBAR INTO UPRIGHTS AS ILLUSTRATED.
- 3) FINALLY, USING THE HEX HEAD BOLTS PROVIDED, FASTEN THE CROSSBAR TO THE UPRIGHTS UNTIL ALL BOLTS ARE SNUGLY FIT.

## **IMPORTANT NOTICE**

THE UNITED STATES CONSUMER PRODUCT SAFETY COMMISSION HAS RECENTLY ADOPTED AND PUBLISHED "GUIDELINES FOR MOVABLE SOCCER GOAL SAFETY". THESE GUIDELINES OFFER INFORMATION ON THE INSTALLATION, USE, AND STORAGE OF FULL-SIZE PORTABLE SOCCER GOALS AND THROUGH THESE GUIDELINES, IT IS THE COMMISSION'S INTENT TO HELP PREVENT SERIOUS INJURIES OR DEATH RESULTING FROM ACCIDENTAL SOCCER GOAL TIPOVER.

SECURELY ANCHORING PORTABLE SOCCER GOALS, AT ALL TIMES, IS ONE IMPORTANT AND EFFECTIVE WAY TO IMPROVE SOCCER GOAL SAFETY. THE PROPER SELECTION OF APPROPRIATE ANCHORING DEVICES IS DEPENDENT UPON A NUMBER OF FACTORS AND IS UNIQUE TO INDIVIDUAL CIRCUMSTANCES. KEY ELEMENTS TO CONSIDER ARE:

- 1) GOAL WEIGHT, INHERENT STABILITY, AND TYPE OF CONSTRUCTION;
- 2) LOCAL FIELD CONDITIONS AND SOIL MOISTURE CONTENT;
- 3) EXPECTED USAGE LEVEL AND OVERALL DEGREE OF FIELD SUPERVISION;
- 4) THE NEED TO RELOCATE OR REMOVE THE GOAL ON A REGULAR OR CONTINUING BASIS.

AS A CHARTER MEMBER OF THE <u>COALITION TO PROMOTE SOCCER</u> <u>GOAL SAFETY</u>, JAYPRO ENDORSES THE EFFORTS OF THE COMMISSION AND OTHERS IN THIS CAUSE. OUR TRAINED SALES STAFF IS AVAILABLE TO DISCUSS THE VARIETY OF GOAL ANCHORS THAT WE OFFER AND TO HELP YOU IN MAKING THE BEST CHOICE FOR YOUR INDIVIDUAL APPLICATION.