

- 1) FOR SAFE OPERATION AND CONTINUED HIGH PERFORMANCE FROM THIS EQUIPMENT. INSPECTION AND MAINTENANCE MUST BE PERFORMED BEFORE EACH USE
- 2) USE OF THIS EQUIPMENT OTHER THAN INTENDED, MAY BE HAZARDOUS.
- 3) ALTERATION OR MODIFICATION OF EQUIP-MENT MAY BE HAZARDOUS. FOR REPAIR OR REPLACEMENT, PLEASE CALL YOUR DEALER

976 Hartford Turnpike Waterford, CT 06385 USA (800)243-0533 (800)988-3363 Fax www.jaypro.com

MODEL NO.: FFHG-12

PRODUCT NAME: FOLDING PRACTICE FIELD HOCKEY GOAL

DRAWN BY: JAC

EFFECTIVE DATE: 1-28-04

JAYPRO SPORTS

FOLDING PRACTICE FIELD HOCKEY GOAL, FFHG-12 LIST OF MATERIALS

PLEASE ENSURE THAT THE FOLLOWING PARTS ARE WITH YOUR ORDER. CLAIMS ON MISSING PARTS WILL NOT BE HONORED AFTER 30 DAYS.

PIECE NO.	PART NO.	<u>DESCRIPTION</u>	QTY.
1	YSG721	SIDE FRAME	2
2	YSG722	UPPER CROSSBAR W/SWAGE	1
3	YSG727	UPPER CROSSBAR	1
4	YSG724	BRACKET	2
5	YSG725	LOWER CROSSBAR W/SWAGE	1
6	YSG726	LOWER CROSSBAR	1
7	HM2905	VALCO PIN (LOCATED INSIDE #2, 3, 5)	4
8	HS5015	HEX HEAD SCREW 5/16" x 2 1/4"	4
9	HN261	LOCKNUT 5/16"-18	4
10	FHND-8	NET	1

ASSEMBLY INSTRUCTIONS

TOOLS REQUIRED: ½" OPEN END SOCKET WRENCH (2) OR ADJUSTABLE WRENCHES (2)

- 1) INSERT UPPER CROSSBAR W/SWAGE (2) INTO UPPER CROSSBAR (3). TO JOIN SIMPLY DEPRESS VALCO PIN BUTTONS AND SLIDE THE END INTO THE CROSSBAR.
- 2) LAY THE SIDE FRAME DOWN AND INSERT THE CROSSBAR. TO JOIN SIMPLY DEPRESS VALCO PIN BUTTONS AND SLIDE THE END INTO THE SIDE FRAME. REPEAT WITH THE OTHER SIDE FRAME.
- 3) POSITION THE BRACKETS (4) ONTO THE SIDE FRAMES AND FASTEN INTO PLACE WITH THE HEX HEAD SCREWS (8) AND HEX HEAD NUT (9). TIGHTEN FIRMLY.
- 4) ATTACH LOWER CROSSBARS INTO THE BRACKET (4) ASSEMBLY. ATTACH LOWER CROSSBAR TO THE BRACKET WITH HEX HEAD SCREW (8) AND HEX HEAD NUT (9). TIGHTEN ALL HARDWARE FIRMLY.
- 5) LAY NET OVER THE OUTSIDE OF THE FRAME AND USE LACING CORD. (NOT PROVIDED)
- 6) STAND GOAL UPRIGHT. IT IS NOW READY FOR USE.

CAUTION: DO NOT HANG FROM CROSSBAR. THIS IS DANGEROUS AND THE EXTRA WEIGHT MAY DAMAGE YOUR EQUIPMENT.